

Ideal for transporting silage, inputs, grains and various products.



Convenience and Efficiency!

- Built in carbon steel, with a simple and resistant chassis, shaped stamped plate, of great robustness and rigidity;
- Rear lid with automatic unlocking, with a full side and vertical opening;
- With support for the use of over-covers;
- Hydraulic cylinder for tilting using hydraulic command of the tractor;



Optional Features

- Grain auger with a diameter of 250 mm
- Hydraulic Brakes.
- Tires.



Technical Specifications

Model	t	Capacity m ³	m ³ /h substituição	Wheel set	Weight (Kg)	Power (CV)	Length (mm)	Width (mm)	Height (mm)	Box dimensions (m)
CFB 5.0	6,2	3,0	5,0	RD 16	975	50	4.500	2.200	2.000	3,0 x 1,8 x 0,6
CFB 5.0	6,2	3,0	5,0	RT 16	1.120	50	4.500	2.200	2.200	3,0 x 1,8 x 0,6
CFB 5.0	6,2	3,0	5,0	RS 16	905	50	4.500	2.100	2.200	3,0 x 1,8 x 0,6
CFB 5.0	6,2	3,0	5,0	RS+RS 16	1.010	50	4.500	2.100	2.100	3,0 x 1,8 x 0,6
CFB 7.0	6,2	4,0	7,0	RD 16	1.040	60	4.500	2.200	2.200	3,0 x 1,8 x 0,8
CFB 7.0	6,2	4,0	7,0	RT 16	1.145	60	4.500	2.100	2.350	3,0 x 1,8 x 0,8
CFB 7.0	6,2	4,0	7,0	RS 16	970	60	4.500	2.100	2.200	3,0 x 1,8 x 0,8
CFB 7.0	6,2	4,0	7,0	RS+RD 16	1.130	60	4.650	2.200	2.300	3,0 x 1,8 x 0,8
CFB 7.0	6,2	4,0	7,0	RS+RS 16	1.060	60	4.650	2.100	2.300	3,5 x 1,8 x 0,8
CFB 9.0	7,2	7,5	9,0	RD 16	1.345	70	5.100	2.350	2.450	3,6 x 2,1 x 1,0
CFB 9.0	7,2	7,5	9,0	RT 16	1.390	70	5.100	2.350	2.600	3,6 x 2,1 x 1,0
CFB 9.0	7,2	7,5	9,0	RS 20	1.330	70	5.100	2.100	2.600	3,6 x 2,1 x 1,0
CFB 9.0	7,2	7,5	9,0	RS+RD 16	1.435	70	5.300	2.350	2.500	3,6 x 2,1 x 1,0
CFB 9.0	7,2	7,5	9,0	RS+RT 16	1.540	70	5.300	2.350	2.600	3,6 x 2,1 x 1,0
CFB 9.0	7,2	7,5	9,0	RT 16.5	1.560	70	5.300	2.350	2.600	3,6 x 2,1 x 1,0
CFB 9.0	7,2	7,5	9,0	RS+RS 16	1.365	70	5.300	2.300	2.550	3,6 x 2,1 x 1,0
CFB 14.0	9,2	9,5	14,0	RT 15.5	2.000	80	6.000	2.500	2.700	4,5 x 2,1 x 1,0
CFB 14.0	9,2	9,5	14,0	RT 20	2.075	80	6.000	2.350	2.800	4,5 x 2,1 x 1,0
CFB 14.0	9,2	9,5	14,0	RS+RD 16	1.830	80	6.400	2.350	2.600	4,5 x 2,1 x 1,0
CFB 14.0	9,2	9,5	14,0	RS+RT 16	1.875	80	6.400	2.350	2.650	4,5 x 2,1 x 1,0
CFB 14.0	9,2	9,5	14,0	RS+RD 20	2.025	80	6.400	2.500	2.700	4,5 x 2,1 x 1,0
CFB 18.0	10,0	10,7	18,0	RT 15.5	2.765	100	6.600	2.680	3.100	5,0 x 2,3 x 1,0
CFB 18.0	10,0	10,7	18,0	RT 20.0	2.840	100	6.600	2.530	3.150	5,0 x 2,3 x 1,0
CFB 18.0	10,0	10,7	18,0	RT 22.5	2.810	100	6.600	2.635	3.200	5,0 x 2,3 x 1,0
CFB 18.0	10,0	10,7	18,0	RS+RT 15.5	2.970	100	6.600	2.680	3.100	5,0 x 2,3 x 1,0