ipacol
parceria de sol a sol

CFB

FORAGE DUMP TRAILER

5.0 / 7.0 / 9.0 / 14.0 / 18.0 / 21.0

Ideal for the transport of silage, inputs, grains and various products.



Practicality and efficiency!

- Made from carbon steel, with simple and sturdy chassis, shaped stamped plate, with great robustness and rigidity;
- Rear tailgate with automatic unlocking, with lateral and vertical opening on CFB 5.0 to CFB 14.0 models and vertical opening on CFB 18.0 and CFB 21.0 models;
- Fitted with mounting supports for upper sideboard extensions;
- Tipping via a hydraulic cylinder, operated through the tractor's hydraulic controls;
- Models CFB 5.0 to 14.0 with a tipping cylinder, CFB 18.0 with one or two cylinders and CFB 21.0 with two cylinders;
- Equipment certified as compliant with NR-12 requirements.













Options

- Grain auger with a diameter of 250 mm.
- Hydraulic brake.
- Tires.

Technical Specifications

Model	Capacity (t)	Capacity (m^3)	Capacity m^3 w/ extensions	Running gear	Weight (kg)	Power (CV)	Length (mm)	Width (mm)	Height (mm)	Box dimensions (m)
CFB 5.0	6.2	3	5	RD 16	975	50	4,500	2,200	2,000	3.0 x 1.8 x 0.6
CFB 5.0	6.2	3	5	RT 16	1,120	50	4,500	2,200	2,200	3.0 x 1.8 x 0.6
CFB 5.0	6.2	3	5	RS 16	905	50	4,500	2,100	2,200	3.0 x 1.8 x 0.6
CFB 5.0	6.2	3	5	RS+RS 16	1,010	50	4,500	2,100	2,100	3.0 x 1.8 x 0.6
CFB 7.0	6.2	4	7	RD 16	1,040	60	4,500	2,200	2,200	3.0 x 1.8 x 0.8
CFB 7.0	6.2	4	7	RT 16	1,145	60	4,500	2,100	2,350	3.0 x 1.8 x 0.8
CFB 7.0	6.2	4	7	RS 16	970	60	4,500	2,100	2,200	3.0 x 1.8 x 0.8
CFB 7.0	6.2	4	7	RS+RD 16	1,130	60	4,650	2,200	2,300	3.0 x 1.8 x 0.8
CFB 7.0	6.2	4	7	RS+RS 16	1,060	60	4,650	2,100	2,300	3.0 x 1.8 x 0.8
CFB 9.0	7.2	7.5	9	RD 16	1,345	70	5,100	2,350	2,450	3.6 x 2.1 x 1.0
CFB 9.0	7.2	7.5	9	RT 16	1,390	70	5,100	2,350	2,600	3.6 x 2.1 x 1.0
CFB 9.0	7.2	7.5	9	RS 20	1,330	70	5,100	2,100	2,600	3.6 x 2.1 x 1.0
CFB 9.0	7.2	7.5	9	RS+RD 16	1,435	70	5,300	2,350	2,500	3.6 x 2.1 x 1.0
CFB 9.0	7.2	7.5	9	RS+RT 16	1,540	70	5,300	2,350	2,600	3.6 x 2.1 x 1.0
CFB 9.0	7.2	7.5	9	RT 16.5	1,560	70	5,300	2,350	2,600	3.6 x 2.1 x 1.0
CFB 9.0	7.2	7.5	9	RS+RS 16	1,365	70	5,300	2,300	2,550	3.6 x 2.1 x 1.0
CFB 14.0	9.2	9.5	14	RT 15.5	2,000	80	6,000	2,500	2,700	4.5 x 2.1 x 1.0
CFB 14.0	9.2	9.5	14	RT 20	2,075	80	6,000	2,350	2,800	4.5 x 2.1 x 1.0
CFB 14.0	9.2	9.5	14	RS+RD 16	1,830	80	6,400	2,350	2,600	4.5 x 2.1 x 1.0
CFB 14.0	9.2	9.5	14	RS+RT 16	1,875	80	6,400	2,350	2,650	4.5 x 2.1 x 1.0
CFB 14.0	9.2	9.5	14	RS+RD 20	2,025	80	6,400	2,500	2,700	4.5 x 2.1 x 1.0
CFB 18.0	10	10.7	18	RT 15.5	2,765	100	6,600	2,680	3,100	5.0 x 2.3 x 1.0
CFB 18.0	10	10.7	18	RT 20.0	2,840	100	6,600	2,530	3,150	5.0 x 2.3 x 1.0
CFB 18.0	10	10.7	18	RT 22.5	2,810	100	6,600	2,635	3,200	5.0 x 2.3 x 1.0
CFB 18.0	10	10.7	18	RS+RT 15.5	2,970	100	6,600	2,680	3,100	5.0 x 2.3 x 1.0
CFB 21.0	14	14	21	RT 15.5	2,800	100	7,000	2,700	3,240	5.5 x 2.3 x 1.2
CFB 21.0	14	14	21	RT 20.0	2,800	100	7,000	2,520	3,240	5.5 x 2.3 x 1.2
CFB 21.0	14	14	21	RT 22.5	2,800	100	7,000	2,855	3,240	5.5 x 2.3 x 1.2