

**Ideal for transporting silage and light products.**

## Convenience and Efficiency!

- ▶ Built in carbon steel;
- ▶ Hydraulic cylinder for tilting, driven by the tractor;
- ▶ Rear cover with vertical or side opening;
- ▶ Removable side covers, facilitating the loading and unloading of products;



## Optional Features

- ▶ Hydraulic Brakes.
- ▶ Tires.

## Technical Specifications

Model	Capacity		Wheel set	Weight (Kg)	Power (CV)	Length (mm)	Width (mm)	Height (mm)	Box dimensions (m) (m)
	t	m <sup>3</sup>							
CAF 5.0	5,0	5,0	RD 16	1.095	50	4.450	2.200	2.250	3,0 x 2,0 x 0,9
CAF 5.0	5,0	5,0	RT 16	1.200	50	4.450	2.200	2.450	3,0 x 2,0 x 0,9
CAF 5.0	5,0	5,0	RS+RD 16	1.205	50	4.600	2.200	2.400	3,0 x 2,0 x 0,9
CAF 5.0	5,0	5,0	RS+RS 16	1.135	50	4.600	2.200	2.400	3,0 x 2,0 x 0,9
CAF 5.0	5,0	5,0	RS 16	1.025	50	4.450	2.150	2.300	3,0 x 2,0 x 0,9
CAF 6.0	6,0	6,0	RD 16	1.315	50	5.000	2.200	2.200	3,5 x 2,0 x 0,9
CAF 6.0	6,0	6,0	RT 16	1.370	50	5.000	2.200	2.450	3,5 x 2,0 x 0,9
CAF 6.0	6,0	6,0	RS+RD 16	1.400	50	5.200	2.250	2.400	3,5 x 2,0 x 0,9
CAF 6.0	6,0	6,0	RS+RT 16	1.510	50	5.200	2.200	2.500	3,5 x 2,0 x 0,9
CAF 6.0	6,0	6,0	RS+RS 16	1.325	50	5.200	2.200	2.400	3,5 x 2,0 x 0,9
CAF 8.0	6,0	8,0	RD 16	1.425	60	5.000	2.200	2.600	3,5 x 2,0 x 1,2
CAF 8.0	6,0	8,0	RT 16	1.480	60	5.000	2.150	2.600	3,5 x 2,0 x 1,2
CAF 8.0	6,0	8,0	RS+RD 16	1.510	60	5.200	2.200	2.700	3,5 x 2,0 x 1,2
CAF 8.0	6,0	8,0	RS+RT 16	1.620	60	5.200	2.150	2.800	3,5 x 2,0 x 1,2
CAF 8.0	6,0	8,0	RS+RS 16	1.440	60	5.200	2.150	2.700	3,5 x 2,0 x 1,2